# **KRASSOCIATES**

House No. 62, By Lane 2, Tarun Nagar, ABC, G S Road, Guwahati 781005 Assam

Date: 03-12-2020

Tø,

The Additional Principal Chief Conservator of Forests (C), Ministry of Environment, Forest & Climate Change, North Eastern Regional Office Law-U-Sib, Lumbatngen Near MTC Workshop, Shillong-793021

SUB.: Submission of six monthly post EC Compliance report in respect of VSK Kiln for clinker (500 TPD) and Cement grinding (500TPD) (closed circuit) units of M/s K.R. Associates, located at Dag 141,142,143,144,145.146 &151 of K.P Patta No. 3,19, 21 & 9 Village Ambher, 12<sup>th</sup> Mile Jorabat, Mouza-Sonapur, Dist- Kamrup, Assam- Environmental Clearance regarding.

REF.: ENVIRONMENTAL CLEARANCE LETTER F. No. J-11011/139/2015-IA.II(I), Dated March 30, 2017.

Dear Sir,

With reference to the Environmental Clearance obtained from MoEF we are hereby enclosing the Six Monthly Compliance Report for the period April'2020 to September'2020 Environmental Clearance issued to us.

I hope that you will find it in order and do the needful.

Thanking You.

Yours faithfully,

For M/s. K. R. Associates.

For K R ASSULL

Modhe hod.

(Partner)

Partner

Copy to:

1. Member Secretary, Pollution Control Board Assam, Bamunimaidam, Guwahati- 21

2. The Regional Director
Zonal Office Central Pollution Control Board, Shillong
"TUM\_ SIR" Lower Motinagar
Near Fire Brigade H.Q. Shillong-793014

# COMPLIANCE REPORT OF ENVIRONMENTAL CLEARANCE FOR THE PERIOD OF APRIL-2020 TO SEPTEMBER-2020

## F. No. J-11011/139/2015-IA. II(I)

## SUBMITTED BY-

M/S. K.R. ASSOCIATES
VILLAGE-AMBHER, JORABAT, MOUZA-SONAPUR,
DIST.-KAMRUP, ASSAM

Name of The Company

M/s. K.R Associates.

**Project** 

VSK Kiln for clinker (500 TPD) and Cement grinding (500TPD) (closed circuit) units of M/s K.R. Associates, located at Dag 141, 142, 143, 144, 145, 146 &151 of K.P. Patta No. 3, 19, 21 & 9 Village Ambher, 12<sup>th</sup> Mile Jorabat, Mouza-Sonapur, Dist- Kamrup, Assam- Environmental Clearance regarding.

Environmental **Clearance Letter**  F. No. J-11011/139/2015-IA.II(I), Dated March 30, 2017.

#### **PART A - SPECIFIC CONDITIONS**

#### **Construction Phase**

Sanctuary at a distance of 1.6 km. As per this Ministry's OM no. J- 11013/41/2006/IA-III (i) dated 2"d December 2009, the PP should obtain prior clearance from Standing Committee of NBWL.  (ii) The project proponent should install 24x7 air monitoring devices to monitor air emissions, as provided by the CPCB and submit report to Ministry and its Regional Office.  (iii) The Standards issued by the Ministry vide G.S.R. no. 612 (E) dated 25th August, 2014 and subsequent amendment dated 9th May, 2016 and 10h May, 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>x</sub> shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw millikin and bag filters to coal mill and cement mill. Low Nox burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard discharge volume. The filter should be replaced at the end of designed life of the filter.	SN.	EC CONDITIONS	COMPLIANCE STATUS
11013/41/2006/IA-III(I) dated 2 <sup>nd</sup> December 2009, the PP should obtain prior clearance from Standing Committee of NBWL.  (ii) The project proponent should install 24x7 air monitoring devices to monitor air emissions, as provided by the CPCB and submit report to Ministry and its Regional Office.  The Standards issued by the Ministry vide G.S.R. no. 612 (E) dated 25th August. 2014 and subsequent amendment dated 3th May. 2016 and 10th May. 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>4</sub> shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Portland Pozzolona	(i)	The project location is in the vicinity of Amchang Wildlife	
obtain prior clearance from Standing Committee of NBWL.  (ii) The project proponent should install 24x7 air monitoring devices to monitor air emissions, as provided by the CPCB and submit report to Ministry and its Regional Office.  (iii) The Standards issued by the Ministry vide G.S.R. no. 612 (E) dated 25th August, 2014 and subsequent amendment dated 9th May, 2016 and 10h May, 2016 regarding cement plants with respect to respect to particulate matter, SO₂ and NO₂ shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/Kiln and bag filters to coal mill and cement mill. Low Nox burners shall be provided to control Nox emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16th November, 2009 shall be followed.  (vii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (xi) The Project proponent shall install filter bags yestem with PTFE discharge volume. The filter should be replaced at the end of designed life of the filter.			is outside the ambit of Amchang Wildlife Sanctuary.
(ii) The project proponent should install 24x7 air monitoring devices to monitor air emissions, as provided by the CPCB and submit report to Ministry and its Regional Office.  (iii) The Standards issued by the Ministry vide G.S.R. no. 612 (E) dated 25th August, 2014 and subsequent amendment dated 9th May, 2016 and 10th May, 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>x</sub> shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control via Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NO <sub>x</sub> burners shall be provided to control NO <sub>x</sub> emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Portland Pozzolona Cement (PPC) and 95 units/none for Ordinary Portland Cement (PPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16th November, 2009 shall be followed.  (vii) AAQ Modelling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (x) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			
monitor air emissions, as provided by the CPCB and submit report to Ministry and its Regional Office.  (iii) The Standards issued by the Ministry vide G.S.R. no. 612 (E) dated 25th August, 2014 and subsequent amendment dated 9th May, 2016 and 10th May, 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>x</sub> shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw millkfuln and bag filters to coal mill and cement mill. Low NO <sub>x</sub> burners shall be provided to control NO <sub>x</sub> emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of vinits/tonne for Portland Pozzolona Cement (PPC) and 95 units/tonne for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vii) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16th November, 2009 shall be followed.  (viii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (viii) Report of proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.		obtain prior clearance from Standing Committee of NBWL.	
to Ministry and its Regional Office.  The Standards issued by the Ministry vide G.S.R. no. 612 (E) dated 25th August, 2014 and subsequent amendment dated 9th May, 2016 and 10th May, 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>x</sub> shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control Nox emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vii) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16th November, 2009 shall be followed.  (viii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (x) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.	(ii)		
(iii) The Standards issued by the Ministry vide G.S.R. no. 612 (E) dated 25th August, 2014 and subsequent amendment dated 9th May, 2016 and 10th May, 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>x</sub> shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kin and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcall/Kg of clinker.  (vii) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16th November, 2009 shall be followed.  (viii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (vi) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume . The filter should be replaced at the end of designed life of the filter.			installed and data is directly transferred to CPCB.
dated 25th August, 2014 and subsequent amendment dated 9th May, 2016 and 10th May, 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>2</sub> shall be followed.  (iv)  Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v)  Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (PPC) and 95 units/tone for Ordinary Portland Cement (PPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi)  The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16th November, 2009 shall be followed.  (vii)  AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii)  Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (viii) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			
May, 2016 and 10 <sup>th</sup> May, 2016 regarding cement plants with respect to respect to particulate matter, SO <sub>2</sub> and NO <sub>x</sub> shall be followed.	(iii)		Agreed with.
respect to respect to particulate matter, \$\tilde{SO}_2\$ and \$\tilde{NO}_x\$ shall be followed.  (iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tone for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.		dated 25th August, 2014 and subsequent amendment dated 9th	
(vi) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tonne for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			
(iv) Continuous stack monitoring facilities to monitor gaseous emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			
emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tone for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.		followed.	
emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tone for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.			
emissions from the process stacks shall be provided. After expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tone for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.			
expansion, limit of PM shall be controlled to meet prescribed standards by installing adequate air pollution control viz Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tonne for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.	(iv)		
standards by installing adequate air pollution control viz Electrostatic precipitators to colinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOX burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.			
Electrostatic precipitators to clinker cooler, bag house to raw mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tonne for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16th November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			
mill/kiln and bag filters to coal mill and cement mill. Low NOx burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			installed to control the air pollution.
burners shall be provided to control NOx emissions. Regular calibration of the instruments must be ensured.  (v) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.			
(vi) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			
<ul> <li>(vi) Efforts shall be made to achieve power consumption of 70 units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.</li> <li>(vii) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16<sup>th</sup> November, 2009 shall be followed.</li> <li>(viii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.</li> <li>(viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.</li> <li>(ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.</li> </ul>			
units/tonne for Portland Pozzolona Cement (PPC) and 95 units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.	( )		
units/tone for Ordinary Portland Cement (OPC) production and thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.	(v)		Noted and being complied.
thermal energy consumption of 670 Kcal/Kg of clinker.  (vi) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume. The filter should be replaced at the end of designed life of the filter.			
<ul> <li>(vii) The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826(E) dated 16<sup>th</sup> November, 2009 shall be followed.</li> <li>(viii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.</li> <li>(viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.</li> <li>(ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.</li> </ul>			
vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.		thermal energy consumption of 670 Kcal/Kg of clinker.	
vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.			
vide G.S.R. No. 826(E) dated 16 <sup>th</sup> November, 2009 shall be followed.  (vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.	(vi)	The National Ambient Air Quality Standards issued by the Ministry	Agreed with
(vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.	(*')		Agrood war.
<ul> <li>(vii) AAQ Modeling shall be carried out to check whether emissions are well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.</li> <li>(viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.</li> <li>(ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.</li> </ul>			
well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.			
well below prescribed standards upon implementation of specific mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.	/	AAA MARKA KANA KANA KANA KANA KANA KANA KANA	A 1
mitigative measures taken up in the existing process and proposed for the expansion.  (viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.  We have installed bag filter, cyclone to control the fugitive emission.	(VII)		
(viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.  Secondary fugitive emission is being controlled by water spraying and plantation.  We have installed bag filter, cyclone to control the fugitive emission.			as Annexure-i.
<ul> <li>(viii) Secondary fugitive emissions shall be controlled and shall be within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.</li> <li>(ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.</li> </ul>			
within the prescribed limits and regularly monitored. Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.  water spraying and plantation.  We have installed bag filter, cyclone to control the fugitive emission.	(viii)		Secondary fugitive emission is being controlled by
Guidelines/Code of practice issued by the CPCB in this regard shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.  We have installed bag filter, cyclone to control the fugitive emission.	(VIII)		
shall be followed.  (ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.  We have installed bag filter, cyclone to control the fugitive emission.			water spraying and plantation.
(ix) The Project proponent shall install filter bags system with PTFE dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.  We have installed bag filter, cyclone to control the fugitive emission.			
dipped PPS felt filter bags, designed to cater for 150% of the air discharge volume .The filter should be replaced at the end of designed life of the filter.	(ix)		We have installed bag filter, cyclone to control the
discharge volume .The filter should be replaced at the end of designed life of the filter.	(,		
designed life of the filter.		discharge volume .The filter should be replaced at the end of	
<u>,, ,                                 </u>	(x)	A statement on carbon budgeting including the quantum of	Point is noted.

SN.	EC CONDITIONS	COMPLIANCE STATUS
	equivalent CO <sub>2</sub> being emitted by existing plant operations, the amount of carbon sequestered annually by the existing green belt and the proposed green belt and the quantum of equivalent CO <sub>2</sub> that will be emitted due to the proposed expansion shall be prepared by the project proponent and submitted to the Ministry and the Regional Office of the Ministry. This shall be prepared every year by the project proponent. The first such budget shall be prepared within a period of 6 months and subsequently it should be prepared every year.	
(xi)	Arsenic and Mercury shall be monitored in emissions, ambient air and water.	Point is noted.
(xii)	Efforts shall be made to reduce impact of the transport of the raw materials and end products on the surrounding environment including agricultural land by the use of conveyors/rail mode of transport wherever feasible. The company shall have separate truck parking area. Vehicular emissions shall be regularly monitored.	Raw materials and end products are transported in covered vehicle. Good condition Vehicle being used to transport the raw material and end product.
(xiii)	Efforts shall be made to further reduce water consumption by using air cooled condensers. All the treated waste water shall be recycled and reused in the process and/or for dust suppression and green belt development and other plant related activities etc. No process wastewater shall be discharged outside the factory premises and 'zero' discharge shall be adopted.	Being a Dry unit water requirement very less. We also adopt 'zero' discharge.
(xiv)	The project authorities should undertake sample survey to generate data on pre project community health status within a radius of 1 Km from proposed mine.	Noted and will be complied.
(xv)	Pre-placement medical examination and periodical medical examination of the workers engaged in the project shall be carried out and records maintained. For the purpose, schedule of health examination of the workers should be drawn and followed accordingly.	Complied with.
(xvi)	Suitable rainwater harvesting measures on long term basis shall be planned and implemented in consultation with the Regional Director, Central Ground Water Board.	Rainwater harvesting structure is under construction.
(xvii)	All the bag filter dust, raw mill dust, coal dust, clinker dust and cement dust from pollution control devices shall be recycled and reused in the process and used for cement manufacturing. Spent oil and batteries shall be sold to authorized recyclers/reprocessors only.	Dust generate from pollution control device is reused in the process. Waste like spent oil is sold to authorized recycler.
(xviii)	Green belt over 33% of the total project area shall be developed within plant premises with at least 10 meter wide green belt on all sides along the periphery of the project area and along road sides etc. by planting native and board leaved species in consultation with local DFO, local community and as per the CPCB guidelines.	Development of green belt is an integral part of our activity. Green belt is being developed as per CPCB guidelines.
(xix)	The project proponent shall provide for solar light system for all common areas, street lights, villages, parking around project area and maintain the same regularly.	Point is noted.
(xx)	The project proponent shall provide for LED lights in their offices and residential areas.	Noted and being complied.
(xxi)	All the recommendations made in the Charter on Corporate Responsibility for Environment Protection(CREP) for the cement plants shall be implemented.	All the recommendations made in CREP for the cement plant is implemented.
(xxii)	At least 2.5% of the total cost of the project shall be earmarked towards the Enterprise Social Commitment based on Public Hearing issues, locals need and item-wise details along with time bound action plan shall be prepared and submitted by constituting a committee comprising of the proponent, representatives of village Panchayat and District Administration. Action taken report in this regard shall be submitted to the Ministry's Regional Office.	Following CSR activity has been done 1. Revamped a local School with various common facilities. 2. Renovated a Church near the plant. 3. Constructed drain in nearby area for proper drainage of water. 4. Paid Rs: 5,00,000/- to the local village committee for development works.

SN.	EC CONDITIONS	COMPLIANCE STATUS
(xxiii)	prepare a detailed CSR plan for the next 5 years including annual physical and financial targets for the existing-cum-expansion project, which includes village-wise, sector-wise (Health, Education, Sanitation, Skill Development and infrastructure etc.) activities in consultation with local communities and administration. The plan so prepared shall be based on SMART (Specific, Measurable, Achievable, Relevant and Time bound) concept. The expenditure should be aimed at sustainable development and direct free distribution and temporary relief should not be included. The CSR plan will include the amount of 2% retain annual profits as provided for in clause 135 of the Companies Act. 2013 which provides for 2% of the average net profits of previous 3 years towards CSR activities for life of the project. A separate budget head shall be created and the annual capital and revenue expenditure on various activities of the plan shall be submitted as part of the Compliance Report to RO. The details of the CSR Plan shall also be uploaded on the company website and shall also be provide in the Annual Report of the	Noted.
(xxiv)	Management Plan along with the mitigation measures shall be prepared with a focus of Disaster Prevention and a copy submitted to the Ministry's Regional Office, SPCB and CPCB within 3 months of issue of environment clearance letter.	Risk assessment study and Disaster Management plant along with mitigation measures has already been prepared and submitted along with EIA report. Copy of the same also sent vide your reply letter Ref No RO-NE/E/IA/AS/IN/80/306-37 dated 16-05-2019.
(xxv)	To educate the workers, all the work places where dust may cause a hazard shall be clearly indicated as a dust exposure area through the use of display signs which identifies the hazard and the associates health effects.	Agreed with.
(xxvi)	Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.	Necessary infrastructure like fuel for cooking, toilets, drinking water etc were provided to the labour at the site during construction phase.

#### **B. GENERAL CONDITIONS:**

SN.	EC CONDITIONS	COMPLIANCE STATUS
i)	The project authorities must strictly adhere to the stipulations made by the Assam Pollution Control Board and the State Government.	Agreed with.
ii)	No further expansion or modifications in the plant shall be carried out without prior approval of the Ministry of Environment, Forests and Climate Change (MoEFCC).	Agreed with
iii)	At least four ambient air quality monitoring stations should be established in the downward direction as well as where maximum ground level concentration of $PM_{10}$ , $PM_{2.5}$ , $SO_2$ and $NO_x$ are anticipated in consultation with the SPCB. Data on ambient air quality and stack emission shall be regularly submitted to this Ministry including its Regional Office at Shillong and the SPCB/CPCB once in six months.	Ambient air quality is monitored and monitoring reports are enclosed as <b>Annexure I.</b> Monitoring data also regularly submitted to MoEF Shillong, CPCB Shillong and PCB, Assam once in six months.
iv)	Industrial wastewater shall be properly collected, treated so as to conform to the standards prescribed under GSR 422(E) dated 19 <sup>th</sup> May, 1993 and 31 <sup>st</sup> December, 1993 or as amended form time to time. The treated wastewater shall be utilized for plantation purpose.	Being a dry unit waste water is not generated. However ETP is installed for laboratory waste water.
v)	The overall noise levels in and around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA Rules, 1989 viz. 75 dBA (daytime) and 75 dBA (nighttime).	The ambient noise level is monitored and noise monitoring reports are enclosed as <b>Annexure-I</b> .

SN.	EC CONDITIONS	COMPLIANCE STATUS
vi)	Occupational health surveillance of the workers shall be done on a regular basis and records maintained as per the Factories Act.	Occupational health surveillance of the workers is be carried out regular basis and records maintain as per the Factories Act.
vii)	The company shall develop rain water harvesting structures to harvest the rain water for utilization in the lean season besides recharging the ground water table.	Rain water harvesting structure is under construction to harvest rain water.
viii)	The project proponent shall also comply with all the environmental protection measures and safeguards recommended in the EIA/EMP report. Further, the company must undertake socio-economic development programmes, educational programmes, drinking water supply and health care etc.	We have complied and implemented all the protection measures recommended in the EIA/EMP report.
ix)	Requisite funds shall be earmarked towards capital cost and recurring cost/annum for environment pollution control measures to implement the conditions stipulated by the Ministry of Environment, Forest and Climate Change (MoEFCC) as well as the State Government. An implementation schedule for implementing all the conditions stipulated herein shall be submitted to the Regional Office of Ministry at Shillong. The funds so provided shall not be diverted for any other purpose.	Agreed with.
x)	A copy of clearance letter shall be sent by the proponent to concerned Panchayat, Zila Parishad/Municipal Corporation, Urban Local Body and the local NGO, if any, from whom suggestions/representations, if any, were received while processing the proposal. The clearance letter shall also be put on the web site of the company by the proponent.	No such suggestions/ representations received from any local body, however EC letter is sent to the gram Panchayat. The clearance letter also placed on the our web site <a href="https://www.galaxycement.com">www.galaxycement.com</a>
xi)	The project proponent shall upload the status of compliance of the stipulated environment clearance conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MOEFCC al Meghalaya. The respective Zonal Office of CPCB and SPCB. The criteria pollutants levels namely; PM <sub>10</sub> , SO <sub>2</sub> , NO <sub>x</sub> (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the projects shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.	The status of EC Compliance and monitoring data is uploaded on our website http://www.galaxycement.com/reports.html and it is sent regularly to MoEF Shilong, CPCB Shillong and SPCB.
xii)	The project proponent shall also submit six monthly reports on the status of the compliance of the stipulated environmental conditions including results of monitored data (both in hard copies as well as by e- mail) to the Regional Office of MOEFCC, the respective Zonal Office of CPCB and the SPCB. The Regional Office of this Ministry at Shillong/CPCP/SPCB shall monitor the stipulated conditions.	Status of the six monthly compliance report and the stipulated environment clearance conditions including result of monitoring data are uploaded in our website i.e <a href="http://www.galaxycement.com/reports">http://www.galaxycement.com/reports</a> and hard copy also sent to the Regional Office of MoEFCC, Zonal Office of CPCB and PCB, Assam.
xiii)	The environmental statement for each financial year ending 31 <sup>st</sup> March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of environmental conditions and shall also be sent to the respective Regional Office of the MOEFCC at Shillong by e- mail.	Noted.
xiv)	The project proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the SPCB and may also be seen at website of the Ministry of Environment, Forests and Climate Change (MOEFCC) at http://envfro.nic.in. This shall be advertised within seven days from the date of issue of the clearance letter at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and a copy of the same should be forwarded to the Regional Office at Shillong.	It was published in two news paper namely "Niamiaya barta" and Eastern Chronicle dated11/04/2017 . Copy of the same is already sent to SPCB, Zonal office CPCB and MoEF Shillong.
xv)	Project authorities shall inform the Regional Office as well as the Ministry, the date of financial closure and approval of the project	The date of approval of the project 14-12-2017. The date of land development work is 01-2-2018.

SN.	EC CONDITIONS	COMPLIANCE STATUS
	by the concerned authorities and the date of commencing the land development work.	
xvi)	The Ministry may revoke or suspend the clearance, if implementation of any of the above condition is not satisfactory.	Agreed with
xvii)	The Ministry reserves the right to stipulate additional conditions if found necessary. The Company in a bound manner shall implement these conditions.	Agreed with.
xviii)	The above conditions shall be enforced, inter-alia under the provisions of the Water (Prevention & Control of Pollution) Act. 1974, the Air (Prevention & Control of Pollution) Act. 1981, the Environment (Protection) Act, !986, Hazardous and Other Waste (Management and Transboundary Movement) Rules, 2016 and the Public Liability & Insurance Act. 1991 along with their amendments and rules.	Agreed with.

\*\*\*\*\*\*\*\*

EC COMPLIANCE REPORT FOR THE PERIOD April'2020 TO SEPTEMBER'2020
ANNEXURE- I
MONITORING REPORTS OF
(AMBIENT AIR QUALITY AND AMBIENT
NOISE)







## TEST REPORT

**AMBIENT AIR ANALYSIS REPORT** 

Report Code: AAQ-1503113\_01\_381

Sample ID: EETNE/AUG/04/2020

Date: 10/08/2020

ULR NO.: TC766920000000140F

Issued to

: M/s. K.R. Associates, Vill: Ambher, Jorabat, Mouza-Sonapur, Dist: Kamrup, Assam.

Sample Drawn By

: UTPAL BEZBARUAH

Sampling Plan & Procedure

: EETNE/SOP/01

**Analysis Duration** 

: 05/08/2020 TO 10/08/2020

**Sampling Instrument Used** 

: AIR SAMPLER/RDS

Pollution Control Device, if any

: NO/YES

SL. NO.	DATE OF SAMPLING	LOCATION/ SOURCE WE		PARAMETERS			
140.			WEATHER	PM <sub>10</sub> (μg/m³)	PM <sub>2.5</sub> (μg/m <sup>3</sup> )	NO <sub>2</sub> (μg/m³)	SO <sub>2</sub> (μg/m³)
i)	0E /08 /3030	Near Main Gate		53.2	32.8	14.7	7.2
ii)	05/08/2020	Near Assam Type House	Clear	57.7	35.0	19.4	10.3

Remarks: - Parameters are within the permissible limit. :- Sampling were done under the annual based.

## NATIONAL AMBIENT AIR QUALITY STANDARDS:

SI.	Pollutant			Concentration in Ambient Air
140.		Test Method	Time Weighted Average	Industrial, Residential, Rural and Other Area
1	Sulphur Dioxide (SO <sub>2</sub> ),	IS:5182 Part-II/	Annual	50
	μg/m³	СРСВ	24 hours	80
2	Nitrogen Dioxide (NO <sub>2</sub> ),	IS:5182 Part-VI/	Annual	40
	μg/m³	СРСВ	24 hours	80
3	Particulate Matter	IS:5182 Part-XXIII/	Annual	60
		(PM <sub>10</sub> ), μg/m <sup>3</sup> CPCB	24 hours	100
4	Particulate Matter		Annual	40
	(PM <sub>2.5</sub> ), μg/m <sup>3</sup>		24 hours	60

For Envision Enviro Technologies North East, Guwahati

Utpal Bezbaruah (Environmental Chemist)

Dr. Pranita Chakraborty
Authorized by (Quality Manager)

Note: i) The results relate only to the parameters tested

ii) The test report shall not be reproduced except in full, without written approval of laboratory.

**Enviro Technologies North East** 

Technologies for better tomorrow

## Recognized by Pollution Control Board, Assam

#### **D.G SET NOISE LEVEL MEASUREMENT REPORT**

Rep.No. 200810\_1503113\_06A\_382

Date: 10/08/2020

Name & Address: M/s. K.R. Associates Vill: Ambher, Jorabat, Mouza-Sonapur, Dist: Kamrup, Assam.

SL. NO.	DATE OF SAMPLING	LOCATION /SOURCE	DG Background Noise	Measured Sound	Actual Sound Pressure Level of DG in dB(A) Leq
i)	05/08/2020	200 KVA - DG Set	59	73.21	73.0
ii)		50 KVA - DG Set	58.3	71.2	70.97

Remarks: Noise level are carried out during day time at a distance 1metre from the enclosure surface.

Method of analysis: CPCB July 2015

Sampling Instrument Used: Lutron SL-4033SD, HTC SL 1350

**DG Set Noise Standards:** 

Noise limit viz. 75 dB(A) at 1m distance.

For Envision Enviro Technologies North East, Guwahati

Utpal Bezbaruah (Environmental Chemist) Dr. Pranita Chakraporty (Quality Manager) (Authorized Signatory)

Note: i) The results relate only to the parameters tested

ii) The test report shall not be reproduced except in full, without written approval of laboratory.

NABL ACCREDITED LABORATORY

### Recognized by Pollution Control Board, Assam

#### AMBIENT NOISE LEVEL MEASUREMENT REPORT

Rep.No. 200910\_1503113\_06A\_383

Date: 10/09/2020

Name & Address: M/s. K.R. Associates Vill: Ambher, Jorabat, Mouza-Sonapur, Dist: Kamrup, Assam.

SL.	DATE OF	LOCATION	NOISE LEVEL in dB(A)Leq		
NO.	SAMPLING	/SOURCE	Day (6:00 am to 10:00 pm)	Night (10:00 pm to 6:00 am)	
i)		Near Main Gate	69.5	63.0	
ii)	05/08/2020	Near Assam Type House	72.2	67.4	

Remarks: Noise level are carried out during 75% of the Day Time & Night Time together.

Method of analysis: CPCB July 2015

Sampling Instrument Used: Lutron SL-4033SD, HTC SL 1350

#### **Ambient Noise Standards:**

Area	Category of area	Limits in dB(A) Leq		
Code		Day (6:00 am to 10:00 pm)	Night (10:00 pm to 6:00 am)	
A	Industrial Area	75	70	
В	Commercial Area	65	55	
С	Residential Area	55	45	
D	Silence Zone	50	40	

For Envision Enviro Technologies North East, Guwahati

Utpal Bezbaruah (Environmental Chemist) Dr. Pranita Chakraborty Authorized by (Quality Manager)

Note: i) The results relate only to the parameters tested

ii) The test report shall not be reproduced except in full, without written approval of laboratory.

NABL ACCREIDITED LABORATORY





## Recognized by Pollution Control Board, Assam

#### **TEST REPORT**

STACK ANALYSIS REPORT

Rep.No. SAR\_1503113\_02\_384/37

Sample ID: EETNE/AUG/04/20

Date: 10/08/2020

ULR NO.: TC766920000000140F

Issued to

: M/s. K.R. Associates, Vill: Ambher, Jorabat, Mouza-Sonapur, Dist: Kamrup, Assam.

Sample Drawn By

Sampling Plan & Procedure

**Analysis Duration** 

Sampling Instrument Used

: EETNE/SOP/01 : 05/08/2020 TO 10/08/2020 : STACK KIT / FLUE GAS ANALYZER

: NO/YES

Pollution Control Device, if any

SL.	DATE OF	STACK DESCRIPTION	PARAMETERS
NO.	SAMPLING	TOTAL BESCHOOLS	Particulate Matter (g/kwhr)
i)	05/08/2020	Stack attached to DG set - 200 KVA	0.19

: UTPAL BEZBARUAH

REMARKS:- Data is within the permissible limit :- Method of analysis: IS 11255 PART-I

**Emission Standards for Diesel Engine for generator set:** 

Engine Power(P)	Parameter	Standards
75KW <p≤800kw< td=""><td>Particulate Matter</td><td>&lt; 0.2 m/lauda</td></p≤800kw<>	Particulate Matter	< 0.2 m/lauda
	i di cicalate Matter	≤ 0.2 g/kwhr

SL. NO.	DATE OF SAMPLING	STACK DESCRIPTION	PARAMETERS
			Particulate Matter (g/kwhr)
ii)	05/08/2020	Stack attached to DG set - 50 KVA	0.26

## Emission Standards for Diesel Engine for generator set:

	Emission Limit (g/kwhr)	
Power Category	Partilulate Matter	
19KW <p≤75kw< td=""><td></td></p≤75kw<>		
- DICH TI E / DICH	≤0.3	

For Envision Enviro Technologies North East, Guwahati

**Utpal Bezbaruah** 

(Environmental Chemist)

Dr. Pranita Chakraborty (Quality Manager) (Authorized Signatory)

Note: i) The results relate only to the parameters tested

ii) The test report shall not be reproduced except in full, without written approval of laboratory.





### Recognized by Pollution Control Board, Assam

#### **TEST REPORT**

STACK ANALYSIS REPORT

Rep.No. SAR\_1503113\_02\_385/371

Sample ID: EETNE/AUG/04/2020

Date: 10/08/2020

ULR NO.: TC76692000000140F

Issued to

: M/s. K.R. Associates, Vill: Ambher, Jorabat, Mouza-Sonapur, Dist: Kamrup, Assam.

Sample Drawn By

: UTPAL BEZBARUAH

Sampling Plan & Procedure

: EETNE/SOP/01

**Analysis Duration** 

: 05/08/2020 TO 10/08/2020

Sampling Instrument Used

: STACK KIT / FLUE GAS ANALYZER

Pollution Control Device, if any

: NO/YES

SL. NO.	DATE OF SAMPLING	STACK DESCRIPTION	PARAMETERS	REMARKS
			Particulate Matter (mg/Nm³)	- Bag filter is attached to
i)	05/08/2020	Stack attached to bag filter of Cement Mill	27.0	Cement mill.

REMARKS:- Data is within the permissible limit :- Method of analysis: IS 11255 PART-I

#### **Emission Standards:**

Parameter	Standards
Particulate Matter	30mg/Nm³

For Envision Enviro Technologies North East,

Utpal Bezbaruah (Environmental Chemist)

Dr. Pranita Chakraborty (Quality Manager) (Authorized Signatory)

Note: i) The results relate only to the parameters tested.

ii) The test report shall not be reproduced except in full, without written approval of laboratory.